

EH1512 Series Enclosure

INDOOR/OUTDOOR

Product Features

- Cost Effective
- Small, Sleek, Contemporary Design
- High Reliability Die-Cast Construction
- Tethered Lid
- Tamper-Proof Hardware (Available as an Option with the EH-SKIT Security Kit)
- Cable Entry Glands and Mounting Holes on Bottom of Enclosure
- Designed for Indoor/Outdoor Applications
- Meets IP66 and NEMA Type 4X Standards
- Easy Access for Servicing and Installation
- Models Available with Factory-Installed Low Power Heater and Blower with 24 VAC Camera Power Supply
- Models with Feedthrough Mount Available
- 3-Year Warranty



EH1512 ENCLOSURE WITH EM1512 MOUNT

The **EH1512 Series** is an indoor/outdoor, cost effective camera enclosure constructed from die-cast aluminum. The **EH1512** has a compact body length of 13.38 (base) and 14.39 (overall) inches (33.99 and 36.55 cm, respectively).

EH1512 Series enclosures are for use with analog and IP cameras having both fixed and variable focal length lenses (with or without auto iris operation). The tethered, removable lid provides easy access to the innovative camera sled. Two adjustable glands (PG9 and PG11) on the bottom of the enclosure allow for easy installation of the power and video cables.

Field-installed options include a heater and blower with 24 VAC camera power supply and sun shroud. The enclosures also can be factory-ordered with 24 VAC, 120 VAC, or 230 VAC heater and blower with 24 VAC camera power supply and sun shroud.

The **EH1512 Series** is ideal for small to medium size analog and IP cameras and can be mounted to Pelco's EM1512 (feedthrough wall mount), EM1450 (non-feedthrough wall mount), or any other Pelco light to medium duty mount.

An EH-MKIT marine kit is available for EM1512 and EM1450 wall mounts. The marine kit protects enclosures and wall mounts from galvanic corrosion.

